

INTRODUCING THE NEW DISTRIBUTION TRUCK SAF-T-ANCHOR

<http://www.oklahomadesigntech.com/saftanchor.html>

PATENT PENDING

COBBLESTONE ANCHORS

The flites on the Cobblestone Anchor are smaller to allow the anchor to maneuver between cobblestones and still provide excellent holding power. There are no compactors on the Cobblestone Anchors (See Page 5).

The Cobblestone Anchor has 4 flites as described below:

- 1" x 5' rod - flites of 4", 3", 2", 2" - CSTAD54322N-1
- 1" x 6' rod - flites of 4", 3", 2", 2" - CSTAD64322N-1

TRUCK ANCHORS

The Truck Anchors have 2 welded nuts, with a bottom nut and welded Kelly Bar stop washer. The 5' anchor can also be installed by hand.

- 1" x 5' rod - flites of 5", 4", 3", 2" STAD55432N-TR-1
- 1" x 6' rod - flites of 6", 5", 4", 3" STAD66543N-TR-1
- 1" x 8' rod - flites of 8", 6", 4", 2" STAD88642N-TR-1
- 1" x 9' rod - flites of 9", 8", 6", 4", 2" STAD98642N-TR-1

The lightweight aluminum **Kelly Bar Anchor Adaptor** is used for the installation of the TRUCK SAF-T-ANCHOR by a line truck or by an easement dolly as seen in the pictures below. The STAD55432N-TR-1 was installed in approximately 1.5 minutes in Class 5 soil. The gauge on the easement dolly indicated it used 525 ft. lbs. of torque.

